

600 Wipe Down Solvent

Thinners & Solvents

Professional Wipe Down Solvent



PRODUCT DESCRIPTION

Professional wipe down solvent designed to remove surface contaminants such as waxes, oils and sanding residues, prior to sanding, surface preparation or paint application

PRODUCT INFORMATION

Colour	ITA075
Specific Gravity	0.74
Volume Solids	0%
Typical Shelf Life	3 years
VOC (As Supplied)	744 g/lit
Unit Size	5 Lt , 200 Lt

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation	Remove dust by using a vacuum or dry compressed air while wiping surface with dry, clean cotton cloths.
Method	Surface should be cleaned using the "Two Cloth Cleaning Method". Soak one cloth in 600 Wipe Down Solvent and use this to wet the surface. Quickly wipe with a dry second cloth to remove the contaminants. The solvent must not be allowed to dry on the surface. Work small areas at a time, so that the second cloth wipes it clean and dry. Repeat until all residue is removed, changing cloths frequently.
Hints	Other Using only one set of cloths or one wet cloth only smears contamination around. Any sanding residue left on the surface can impair the finish.
Compatibility/Substrates	Do not use as a thinner or reducer

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	TRANSPORTATION: 600 Wipe Down Solvent should be kept in securely closed containers during transport and storage. STORAGE: Exposure to air and extremes of temperature should be avoided. For the full shelf life of 600 Wipe Down Solvent to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.
----------------	--

Safety	DISPOSAL: Reminders of 600 Wipe Down Solvent cannot be disposed of through the municipal waste route or dumped without permit. Disposal of reminders must be arranged for in consultation with the authorities.
---------------	---

IMPORTANT NOTES	<i>The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.</i>
------------------------	---

Please refer to your local representative or visit www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2019.